# **PhoneLink**

# Telephone Entry System



The American Access Systems, Inc **PhoneLink** telephone entry system is constructed using a heavy gauge, powder coated enclosure and stainless steel faceplate and is designed to be either post or surface mounted.

Functions available with the **PhoneLink** allow the user to conveniently screen entrants from the security of a telephone inside the home or office. When a guest presses the call button, a double ring alerts the people inside that someone is at the gate, rather than an incoming telephone call. Access is allowed by simply pressing \* \* for a momentary relay operation, or \* # to latch the gate open. The gate can be called and latched open without a guest being present at the gate.

This system features a "one-shot" code, which enables the user to safely give out a code for one time use only. Additional features include call waiting, call forwarding, full programming capability from the interior telephone, a manual override providing phone switching in the event of damage to the telephone entry unit and an optional pinhole camera for additional security. For the guest with pre-authorized entry, a fully programmable 500 code keypad is provided.

The **PhoneLink** telephone entry is a "No Phone Line" telephone entry system, allowing you to use your existing telephone line without creating an addition to the phone bill.



# **PhoneLink**



16-2050

### **General Specifications**

- Input: 12 VAC or VDC (Transformer included)
- Output: n/o or n/c contact 1 -99 second
- Operating temperature: -15 to 175 Fahrenheit
- Dimensions: 7 3/8" H x 7 3/8" W x 5" D
- 8 ohm Mylar speaker w/ call button
- Ship weight: 9 lbs.
- 3000 ft. range
- Less than 45 mA draw (without nightlight)

## **Relay Specs**

	DC Load	AC Load
Contact Rating	2A @ 30V	.5A @ 125V
Max. switching voltage	125V	125V
Max. carrying current	2A	2A
Max. switching power	60W	62.5VA

#### **Features**

- 500 access code capacity
- Programmable Personal Master Code
- Programmable Latch / Sleep Code
- Programmable "One -Shot" Code
- Fully programmable from telephone
- 2 relays
- Adjustable volume:
  - microphone, speaker & phone tone
- Event Input
- Night Light
  - "60 second on" capability
- · Optional camera
- Unique double ring cadence
- Call waiting
- Call forwarding
- Call button disconnect
- By-pass switch included

### **Manufactured by:**

American Access Systems, Inc 7079 S Jordan Rd. Unit 6 Centennial, CO 80112

ph: (800) 541-5677 fx: (303) 799-9756

www.americanaccess.com

#### **Distributed by:**