



# 1803 AUTO DIALER TELEPHONE INTERCOM SYSTEM



flush mount



surface mount



**built-in display**  
indicates door/gate has  
been opened



**telephone access**  
systems use a modular design  
concept that makes installation  
and service easy



**dtmf tone output**  
allows these systems to be used  
with PBX, KSU and telephone  
systems with auto-attendants



**two mounts**  
surface and flush are available


- Provides visitor access control into apartment buildings, gated communities, condominiums, office buildings, factories and industrial sites
- Visitors use the 1803 to communicate with a resident, who can then grant or deny them access from their touch-tone telephone
- Provides service for up to 1000 residents
- Programmable directory codes can be set from 1 to 4 digits
- Surface or flush mount styles available

FEATURES



ACCESS CONTROL SOLUTIONS



The model 1803 is an ideal telephone entry system that is suited for applications that do not require a directory, or in applications where a separate directory exists. Visitors are easily identified by voice communication and can be granted or denied access directly from a touch-tone telephone.



**1803 Surface**  
11.25" W x 13" H x 4.5" D  
28.5cm W x 33cm H x 11.43cm D



**1803 Flush**  
12" W x 13.25" H x 3" D  
30.4cm W x 33.65cm H x 7.62cm D



## 1803 Specs

### Communication

True full duplex  
Hands free  
Optional handset available (ADA compliant) on surface mount units only

### Display & Mounting Styles

Surface or flush mount  
Display for programming assistance and shows 'open' when access is granted

### Capacity

1000 phone numbers, 10 area codes  
4 digit entry codes same as system memory  
5 digit entry codes = 6

### Door/Gate Control

Two relays allow for control of both a vehicular gate and a pedestrian gate

### Programming Methods

System keypad  
Touch-tone telephone

### Advanced Features

Programmable directory codes can be set from 1 to 4 digits in length  
10 & 11 digit dialing capability  
LCD Programming display  
Built in clock/calendar  
Time clock has its own backup power source  
Entry code time zones  
Four hold-open time zones  
Flash entry codes  
DTMF tone output allows for use with KSU, PBX and systems with an auto-attendant  
Two special inputs can be programmed for relay activation or dial-out function  
Time zone restrictions on selected entry codes  
Built-in postal lock provision

### Options

Gold-plated faceplate available on flush mount style only  
Fluorescent light kit  
Heater kit - recommended when temperatures routinely fall below 10°F (-12°C)  
Camera Ready:  
Optional B&W or Color CCTV camera\*  
\*may require additional CCTV equipment

### Operating Temp

10°F to 145°F  
-12°C to 62°C  
Optional heater kit available for colder climates

### Electrical Requirements

16 VAC, 20 VA System power (250 ma)  
U.L. listed power transformer provided  
Ringer equivalence: 0.0A Jack Type: RJ11C or W

### Safety Standards

FCC (US) DUF6VT-12874-OT-0  
DOC (CAN) 1736 4507 A  
Complies with UL 294  
ETL Listed

### Shipping Weight

Approximately 15-20 lbs (6.8-9 kg)

### Warranty

2 year limited factory warranty

Distributed by:

### DOORKING, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A. Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2008 All Rights Reserved. Product specifications may change without notice. Rev. 8/08

### MEMBER:

