STAND ALONE PRX-320

Water-Proof Proximity/Keypad Access Control

PRX-320

- Stand-alone unit is appropriate for use on gates or doors where there is need for resistance to climactic conditions.
- Powered by 12V DC supply
- Can be used on solar installations
- Has the option of using a built-in contact for doorbell enunciators.
- Use it as a keypad for some users and as a proximity card reader for others.



4564 Johnston Parkway Cleveland, Ohio 44128

Telephone:

1-800-426-9912 or

216-518-9888

Fax: 216-518-9884

Email: salessupport@emxinc.com

Web: www.emxinc.com





PRX-320
Proximity & Keypad Control
L=5.0" x W=2.75" x D=1.4"



CARX-20 Access Card Reinforced L=3.4" x W=1.2" x H=0.1" (ISO Standard size)



PRX320-PAD Mounting Adaptor Plate L=6.0" x W=4.0" x D=.5" Polypropylene



PED-001
Gooseneck stand

SPECIFICATIONS

Power Requirements: 12 VDC 500-800 mA

Power Consumption: 90 mA standby / 110 mA activated

Relay Contact Rating: 3A /12VDC

Power Indicator: RED LED Bar on Constant Key Confirmation: Green LED On while key is

depressed

Entry Confirmation: Green LED Bar On for set time

Entry Denied: Yellow LED flashing
Alarm condition: Yellow LED constant

Read Range: 5 inches

Access: Up to 2000 users by card or 8

user passwords

Programmable door lock settings