

FCI4000

WiFi Video Intercom



Relay outputs

2

Camera:

Color 640x480



- Simple setup by mobile phone
- Connect to the intercom directly through your phone's Wi-Fi, enter the pass code for the home hub Wi-Fi and the device is connected
- View the gate/door and open any time with monitoring mode
- Full duplex speech
- 2 relay output
- Latching outputs for hold open.
- CAT5 terminal port for easy hard wire option
- Upgraded camera with IR cut filter for better color by day and IR night vision by night
- Stores images of the last 32 missed callers on your phone
- High gain waterproof Wi-Fi antenna for extended range
- Still works locally on Wi-Fi network even if broadband goes down

TECHNICAL SPECIFICATIONS

App name	WIFI PRO 2
Power supply	24v dc (adaptor included)
Power consumption	80mA standby - 300mA during call
Relay outputs	2
Keypad option	Yes
Keypad codes	1200
Keypad relays	3
Relay type	N/C and N/O contacts
Relay load	2A - 24v AC max
Relay time	Adjustable 1-10 seconds
Audio	Full 2 way Duplex and half Duplex sound options
Wi-Fi standard	802.11b/g/n
Wi-Fi antenna	Directional 60°; Waterproof for outdoor use
Security	6 digit passcode protected
Uplink bandwidth	110K bits/sec
Camera	Color; 110 degree, 640x480 pixel
Night vision	Yes, by infrared illumination (with IR cut filter)
Operating ambient temperature	-22°F - 110°F (-30°C - +50°C)
Weight	4.7 lb (2.1 kg)
Dimensions (L x D x H)	9. x 7 x 3.5 in (229 x 180 x 90 mm)
Protection class	IP 55
Enclosure	BS316 marine grade SS construction with gloss black face trim

FEATURES



Google™
PUSH alerts
on Apple
and Android
devices



Icon
based
layout



Google cloud messaging



2 relays



Full 2 way Duplex and
half Duplex sound options!



Camera with IR cut
filter for better color
by day and better IR
night vision by night

MODEL NUMBER

Model	Part No.
Wi-Fi Intercom with video	4402

DIMENSIONS (INCHES)

