

GATE AND DOOR ACCESS CONTROLS

Wireless 3-Button Control Station

WPB3LM



*Wireless 3-Button
Control Station -
WPB3LM*

SIMPLE WIRELESS PUSH BUTTON CONTROL

Simple to install and easy to use, the new LiftMaster® Wireless 3-Button Control Station offers extended functionality of battery power, immunity from lightning strikes and secure digital encryption. Cover it all with a warranty unlike anything in the marketplace, and we are sure that this will be your choice for "exit control" whenever you need it!

The UltraRX MicroPower 4-Channel 900MHz Receiver includes (3) Form "C" (10-amp 277V AC) relays with optional (normally open or normally closed) outputs. There is no other product of this type available on the market. Compatible with the LiftMaster® Logic 3.0 Technology for Elite Series™ Commercial Door Operators (see back side for additional information).

ONE YEAR WARRANTY

COMPATIBILITY

- UltraRX- Extreme Range Receiver (ULTRX9003)
- LiftMaster Logic 3.0 Operators

CHAMBERLAIN®

LiftMaster®

WIRELESS ACCESS AND COMMUNICATION SYSTEMS

- Completely Wireless
- 1,000-Foot Range (Typically 300'-700')
- Operates up to 5 Years on (4) AA Batteries

- UV Hardened Polycarbonate Enclosure
- Pedestal or Surface Mount
- Eliminates Trenching

- Invisible to Lightning
 - Secure Digital Encryption
 - USA Designed and Made
- Patent Pending*



LIFTMASTER® LOGIC 3.0 TECHNOLOGY

Elite Series™ Commercial Door Operators are engineered, manufactured and tested to provide reliable service to meet the toughest commercial applications.

Added Value:

- Built-in 3-channel, 315MHz radio receiver lets you add as many as 23 Security+® or unlimited DIP switch remote controls.
- All LiftMaster 3-button remotes can be programmed for open/close/stop operation.
- Improved Maintenance Alert System™ lets you establish a routine maintenance schedule based on the number of cycles or calendar date. Includes self-diagnostic system that allows you to troubleshoot up to 8 different error codes.
- Timer may be set to close in 5-second or 1-minute increments. LED flashes to show timer countdown.
- Thermal motor overload can now be easily reset from the 3-button floor-level station.
- Programmable mid-stop allows door to stop at mid-point during open travel.
- Programmable maximum run timer signals door to reverse or stop if closing time exceeds maximum by more than 10 seconds.

Reliability:

- Switchless motor eliminates stuck start switch and motor malfunctions on single-phase operators, the industry's #1 cause of motor failure and callbacks.
- All high-voltage connections have been removed from the board for safer installation and improved reliability.
- 1-1/2 second delay-on-reverse helps prevent door and operator wear.

Programming Simplicity:

- Selector dial replaces DIP switches for selecting wiring types and programming.
- Selector switch for failsafe and non-failsafe wiring types.
- Diagnostic LEDs speed installation and troubleshooting of more features including photo-eyes, mid-stop, timer and timer defeat.
- Motor direction jumper lets you change motor direction by simply moving a jumper.

Logic 3.0 Technology Available on Models:

T, GT, APT, HCT, J, DJ, DH, H, GH, SD, GSD



CHAMBERLAIN®

LiftMaster®