

Emergency Call Stations SAT3 / SAT3R



SAT3 with Hood

SAT3 Standard Features:

- Central Station compatible (SIA Fast Format).
- Telephone line powered.
- 1200 baud modem for programming is included.
- Calls both central station and regular telephone numbers, in any order.
- “Push for Help” calls up to 10 pre-programmed phone numbers (16 digits each).
- Calls can only be ended by the called party, time out or call progress signals.
- Can be called for programming, monitoring, testing and controlled remotely (password protected).
- 3 ways to program:
 - 1200 baud modem with menus
 - Hand held programmer
 - Touch tone telephone
- Senses full call progress signals.
- Location can be identified by Account number with Zone (SIA Fast Format) or DTMF.

- A.D.A. compliant.
- New high intensity LED's (sunlight viewable) for Calling & Talk.
- Braille available for the sight impaired.

SAT3R (relays):

- The SAT3R includes 2 Form C relays (requires transformer, included with “R” model).
- All other SAT3R functions remain exactly the same as the SAT3.

SAT3D / SAT3DR INFORMATION MODELS:

- Additional “Information” button, for the SAT3 and SAT3R that will call a single 16 digit telephone number for information or support. (product not shown)



SAT3R

SAT3

- Central Station compatible with SIA Fast Format.
- 1200 baud modem included in all SAT3, SAT3R and SAT3D's.
- Telephone line powered.
- When "Push For Help" button pressed, the SAT3 dials a pre-programmed 16 digit telephone number.
- Automatic redial when unit senses line busy, circuit busy or no answer, (up to 9 additional phone numbers of up to 16 digits each can be pre-programmed for redialing).
- Central station format: Account Code may be 4 to 8 digits, Account Zone is 4 digits providing 1000 Zones.
- Dials extensions (works behind PABX), local or long distance numbers, (any combination for redialing).
- Automatic transmission of account code or upon command DTMF.
- Location can be identified by Account Code with Zone Number in SIA Fast Format or DTMF.
- Sunlight viewable high intensity LED's for call progress indicators (CALLING & TALK for ADA compliance).
- Optional Braille for ADA compliance.
- SAT3 senses full call progress signals: dial tone, fast busy, busy, ring back, off hook alert, power denial and line reversal.
- Programmed talk time (1 to 9 or 20 minutes) may be extended by the called party.
- Remote programming via (1) touch tone telephone (2) hand held programmer (3) dial-up with 300/1200 baud modem with menu. (Pass Word Protected)
- Auto answer and activation from remote location (Pass Word Protected).
- Remote hang up.
- Weather resistant housing.

SAT3R

- Relay model available (2 Form C relays), transformer provided for relay activation, (flashing light, camera activation, open a door or gate, etc.)
- All other functions of the SAT3R are the same as the SAT3.

SAT3D and SAT3DR

- These models also provide a second button that can be pre-programmed for a single 16 digit telephone number for information or support.
- All other functions of the SAT3D are the same as the SAT3.

MULTIPLE MODELS AVAILABLE:

Standard -SAT3
Standard Flush Mount-SAT3F
Standard with Weatherhood-SAT3H
Standard Flush Mount Elevator-SAT3FE
Relay version-SAT3R
Relay version with weatherhood-SAT3RH
Relay version Flush Mount-SAT3RF
Relay version Flush Mount Elevator-SAT3RFE
Standard with information button-SAT3D
Standard with information button in Flush Mount-SAT3DF
Standard with information button with Hood-SAT3DH
Standard with information button and Flush Mount Elevator-SAT3DFE
Relay version with information button-SAT3DR
Relay version with information button and hood-SAT3DRH
Relay version w/ information button & Flush Mnt. Elevator-SAT3DRFE

SYSTEM ENHANCEMENTS

- MUI (multiple unit interface).
- Receiver (SATDBRX) for SAT units.
- Stainless steel outer shell.
- Color and graphics upon request.
- **POWER REQUIREMENTS:** SAT3 is telephone line powered only. SAT3R telephone line power and 12 volt transformer supplied for relay board.
- **MATERIALS:** Double wall aluminum shell with stainless steel faceplate, (stainless steel shell optional).
- **MOUNTING:** Surface, flush or post.
- **TOUCH TONE DETECTION:** Detects short burst 50 ms DTMF tones.
- **RINGER EQUIVALENCE:** .5A - 1.8B
- **FCC REG.:** CCPW74F-17213-MT-E
- **SHIPPING WEIGHT:** Approx. 5 lbs.
- **OPERATING ENVIRONMENT:** Temp. -20°F to +140° F (6°C to 60°C); Relative humidity: 5% - 95% non-condensing.
- **DIMENSIONS:**

SAT3	5"W x 7 5/8"H x 2 1/2"D
SAT3R	6"W x 8 1/2"H x 2 1/2"D
SAT3H	5"W x 9 1/2"H x 2 1/2"D
SAT3FE	Fits selected elevator opening
SAT3R	5"W x 9 1/2"H x 2 1/2"D
SAT3RF	5"W X 10 1/2"H X 2 1/2"D
SAT3RH	5"W X 7 5/8"H X 2 1/2"D bot 3/4"D top
SAT3RFE	Fits selected elevator opening.
SAT3D & SAT3DR	Contact the factory.

APPLICATIONS:

- Walkways
- Stairwells
- Information phones
- Access control
- Surveillance with camera control
- Elevator control
- Computer rooms
- Parking garages
- Factories / Commercial use
- Retirement homes
- Condominiums / Townhouses

"Select...Don't Settle"



06/07