

# *Basic Telephone Entry*

**TEC1  
TEC1C  
TEC1CA**

## STANDARD FEATURES:

- TWO ENTRANCE RELAYS
- NO SUNSHIELD NEEDED TO READ LCD DISPLAY
- LCD DISPLAY BACKLIT FOR NIGHT VIEWING
- BOARD LEVEL SURGE PROTECTION
- TRANSFORMER INCLUDED
- PROGRAMMABLE VIA KEYPAD OR WITH OPTIONAL MODEM AND SOFTWARE (TEC1CA)
- DISPLAY WORKS IN COLD OR HOT WEATHER:  
-0F to +158F
- WEATHER RESISTANT HOUSING
- TWO YEAR LIMITED WARRANTY \*



TEC1 Shown with Nite Lite Hood on pedestal.



## OPTIONS:

- NITE LITE WEATHER HOOD
- SEMI FLUSH MOUNT RING
- MULTI - UNIT INTERFACE
- PINHOLE B & W OR COLOR CAMERA
- 12VDC STANDBY BATTERY
- ALLIANCE VOICE PROCESSOR — NO PHONE BILL SYSTEM
- PEDESTALS AND MOUNTING PLATE

The TEC1 provides basic telephone entry with the SES advantage. TEC1 is offered in four capacities: 50, 125, 500 and 995 to match your requirements and has optional card access capability. All systems come with 2 relays standard and have a two line LCD directory display that is easily read in direct sunlight or at night. As with all SES telephone access systems, the TEC1 has board level surge suppression at no additional cost, and the stainless steel front door and aluminum back box are sure to provide years of faithful service. Designed to the same high standards as the TEC and CAT product lines, the TEC1 comes with a two year limited warranty.

TEC1, the best of basic telephone entry, with unmatched SES quality.

*"Select...Don't Settle"*



**ACCESS CONTROL**

### FEATURES — ALL MODELS

- Two line LCD display readable in direct sunlight or darkness.
- System programmable code length from 1 to 6 digits for codes and PINs.
- Programmable Entry PIN code attempts (strike out) from 0 to 9 tries.
- Programmable Hide-a-Name feature to conceal resident identities.
- Provides two door control relays.
- Ability to latch relay or provide remote door release through telephone touch tones.
- REX inputs for both entrance control relays.
- Dials out up to 14 digit telephone numbers tone or rotary.
- Talk time programmable from 1- 99 minutes.
- Programmable voice mail response via active keypad.
- Mutes tones in speaker while dialing.
- Blocks door open tone through microphone.
- Fully programmable through the keypad.
- Non-volatile memory.
- Programmable background “beep” to indicate incoming call is from TEC1.
- Integrated surge protection on all inputs and outputs to minimize transient voltage effects.
- Postal lock capability included.
- Surface or pedestal mounting.
- Manager Password.
- Battery charging circuit.
- 2 year limited warranty.

#### **TEC1C** - All of the above features plus:

- Weigand 26-bit card-capable, supports two card readers. Card capacity of system matches memory size of TEC1C.

#### **TEC1CA** - All of the above features plus:

- Clock, calendar, modem and software included. Card capacity of system matches memory size of TEC1CA.

### SPECIFICATIONS

- Outside dimensions:  
8 1/2"W x 113/4"H x 3 1/2"D
- Shipping weight: Approx. 11 lbs.
- Power: 16.5VAC 20VA transformer (supplied).
- Construction: stainless steel front door, with aluminum back box.
- Operating environment:  
Temperature: - 0F to 158F  
Relative humidity: 5% to 95% non-condensing
- Memory type: non-volatile
- Relay type: Form A or B dry contact rated 24 V @ 3 AMPS.
- Tone detection: crystal controlled, will detect short burst 50 ms tone.

### OPTIONS

- Multi-Unit Interface - MUI - allows up to 4 TEC1's to share phone line.
- Pin hole camera - B & W or Color.
- LED lighted stainless steel weather hood
- Standard stainless steel weather hood
- Semi-flush mount ring
- Back box stainless sleeve
- Handset (specify length)
- Standby battery
- Pedestals and adapters
- No Phone Bill System - Alliance Voice Processor

### APPLICATIONS

- Apartment complexes or condos
- Gated communities
- Office buildings and garages

*“Select...Don't Settle”*



1 (800) 342-5737 (305) 823-5410 Fax: (305) 823-5215  
Web site: [www.selectses.com](http://www.selectses.com)

7991 West 26th Avenue Hialeah, Florida 33016  
Sales: [sales@selectses.com](mailto:sales@selectses.com)

0607