VIKING ACCESS SYSTEMS**

COMPACT AND EFFICIENT DC POWERED AUTOMATION







RESIDENTIAL AND COMMERCIAL

SLIDE GATE OPERATOR

CLASS I, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR




09VISSELLSHEETS.indd 17 10/16/09 5:49 PM

K-2™ PRODUCT INFORMATION AND SPECIFICATIONS

The K-2[™] slide gate operator raises the bar in quality for the residential market. This machine operates a highly efficient direct motor drive which allows operation at 100% duty cycle. This assures efficiency and reliability. The fail-safe, fail-secure options of the K-2[™] gate operator allows it to handle gates up to 650 lbs. in conformance with UL 325 and UL 991 Type I, III and IV. This operator is UL Listed 18TC UL325 and UL991.



On-board lightening protection



Innovative fine tune adjustment for the end of gate travel (down to 1/8")

Back-drivable unit features direct drive mechanism



Soft-Stop / Soft-Start with intelligent Obstruction Detection





Built in optional auto-open feature in case of power failure

120 / 220 VAC single phase power source



VIKING BLUE ENABLED

SOLAR EFFICIENT OPERATION





800.908.0884 vikingaccess.com



Operational Voltage ... 24 VDC with 1/2 H.P. Motor ... 120 / 220 VAC Single Phase **Main Power Source** ... 7 AmpHr 12 VDC x 2 **Battery** ... 650 lbs. / 27 feet **Max Gate Capacity Max Operating Speed** ... 12" per second **Battery Backup Operation** ... 100 Full Cycles (650 lbs. / 20' gate) Max Duty Cycle ... 100% Continuous Cycle **Operating Temperature** ... - 4° F to + 158° F

5 YEAR RESIDENTIAL WARRANTY

1009VISSELLSHEETS.indd 18 10/16/09 5:49 PM