

Wiegand Output Radio Reader Model WOR

- **Easy way to equip ANY Wiegand input access control panel with radio transmitter access.**
- **Connects as easily as card readers; transmitters are added like cards, with no software changes required.**
- **Keyless entry offers user convenience, safety, and security for triggering gates, barrier arms, and doors.**
- **Ideal way to facilitate handicapped access.**
- **Multi-button transmitters can double as personal emergency devices for triggering security alarms.**
- **RF input/Wiegand output receiver supports 26, 30, or 31-bit data formats.**
- **Wide selection of MegaCode (over 1 million codes) format transmitters, with available block coding.**
- **Field adjustable read range—from 5 to to 500 feet.**
- **Facility and ID codes tailored to system requirements.**
- **Weather-resistant case for mounting outdoors or in.**

Any existing access control system can be equipped with radio-based proximity sensing, by the simple addition of Linear's Radio Reader (Model WOR). Keyless entry, handicapped access, and emergency alert functions are easy to achieve with this wireless control technology.

With a read range of up to 500 feet, Linear transmitters facilitate handicapped access far more than close proximity or contact devices. For adding security at sites such as college campuses and parking garages, multichannel models allow access control and "panic button" functions to be combined in a single device.

The WOR uses a Wiegand output format (26, 30, and 31-bit supported) that interfaces to virtually any commercial access control panel. Long-range transmitters can be added as easily as Wiegand cards, and without software changes. Facility and ID codes can be matched to system requirements.

The 500 foot range of the WOR is made possible by superheterodyne receiver technology. It is supplied with a local whip antenna that screws directly onto the receiver's top connector. Two remote antennas are also available: the directional EXA-2000 or the omni-directional EXA-1000, both of which wire to the receiver's antenna connector with type RG-59 cable. An integral gain control is included to limit the maximum radio range that the WOR can achieve, if required.

A two-color LED acts as a status display. It lights red when the receiver is getting dc power from the system controller and turns green when access is granted to a transmitter. The radio LED lights when the receiver detects a transmission and can be used for troubleshooting and verifying system performance. Receiver test points are provided for listening to incoming signals.

The WOR is housed in a weather-resistant enclosure, so it can be mounted outdoors or inside. Gaskets and a weather-tight wiring strain relief seals the unit from the elements.



General Specifications

RADIO FREQUENCY

Frequency: 318 MHz

Bandwidth: 300 KHz minimum

Image Rejection: 40 dB

LO Reradiation: 200 μ V/meter @ 3 meters (maximum)

Data Format: MegaCode

Sensitivity: -100 dBm minimum

Sensitivity Adjustment: 20 dB variable attenuation at the antenna input

INPUTS

Power: terminal block input “+” and “Gnd”; input voltage operation 5 Vdc regulated or unregulated between +6 to +24 Vdc with reverse polarity protection

Hold: terminal block input “Hold”; follows standard Wiegand hold line conventions; hold line can be overridden via dip switch

Antenna: 9-1/2 in whip antenna with F-connector (supplied)

OUTPUTS

Data: terminal block output “Data 0” and “Data 1”; standard Wiegand electrical and protocol interface

LEDs: Red RF activity LED indicates RF activity at 318 MHz; red/green decode LED is green during Wiegand data transmissions and receiver hold timing window (if enabled) after any output transmission, otherwise it is off unless hold enable is selected, in which case LED will remain red until hold is removed by host system

CONTROLS

Pushbutton: momentary switch labeled “Program” used to configure microprocessor after system option selection and configuration

Dip Switches:

Receiver Facility Code: four positions to select 1 of 16 possible MegaCode facility codes; if code 0 is selected, the receiver will validate any received facility code; any other selection requires the transmitters’ facility code to match the receiver facility code selection for validation

Output Facility Code: 16 positions to select one of 65,536 possible facility codes; a selected output format may not use all 16 bits

Output Format: 3 positions for selecting either 26-bit, 30-bit, or 31-bit Wiegand output format

Button Disable: 5 positions, each corresponding to 1 of 5 possible MegaCode transmitter buttons — left or top left, right or top right, bottom left, bottom right, top

Receiver Lockout Disable: 1 position; if set to ON, the 1 second receiver lockout is not performed

Button Offset: 1 position; if set to ON, the transmitter ID number is offset with a number based on which button is pressed:

Button	Offset
Left	0
Right	16384
Top	32768
Bottom Left or Right	49152

ENCLOSURE

Weather-resistant, anodized aluminum enclosure with removable end caps to provide wiring and programming access; end caps secured with screws

OPERATING TEMPERATURE

-22° to +155°C (-30° to +70°C)

ELECTRICAL

Robust RFI and ESD protection for all inputs and outputs, including antenna input; protection to prevent output errors during brownouts

WIRING

Five conductor cable up to 300 feet, BELDEN 9929 or equivalent (24 AWG); up to 500 feet, WEICO 9404 or equivalent (20 AWG); up to 1,000 feet, CAT-5

AVAILABLE ACCESSORIES

Antennas:

- EXA-1000:** remote, omnidirectional; includes mounting hardware and five feet of cable
- EXA-2000:** remote, directional-type; including mounting hardware and ten feet of cable

Linear®

1950 Camino Vida Roble, Suite 150
Carlsbad, CA 92008

(760) 438-7000 (800) 421-1587 Fax (800) 468-1340

www.linearcorp.com