

## Alpha 550 24V DC

## **ELECTROMECHANICAL SWING GATE OPERATOR STRONG,** SECURE AND EASY TO INSTALL FOR RESIDENTIAL USE







- High quality electromechanical operator for leaf lengths of max. 5,5 m / 18 feet
- Simple and fast installation, thanks to a front lid hiding the power cable terminal
- Strong die-cast aluminum body for longer
- 550 for max. leaf length of 5,5 m / 18 feet
- adjustable, mechanical stop in opening and closing . Long Stroke
- Emergency batteries and KIT SUNNY solar panel for recharge can be applied
- Stainless steel rod
- On request version without housing for installations closer to the gate tip
- Duty Cycles\*: 30 per hour.
  - \* Duty Cycles depend on gate size and installation

Dimensions (inches) 45 7/10

C (stroke)

15 4/5







Release with special key (optional) Oscillating front bracket for down hill installations

CODE	DESCRIPTION	MAX LEAF WEIGHT	MAX LEAF LENGTH	MAX OPENING DEGREE	MAX CYCLES / HOUR	PCS PER PALLETS
10955240D-1-CSA	ALPHA 550 24V DC right	1100 lbs	18 feet	120°	30	24
10955240S-1-CSA	ALPHA 550 24V DC left	1100 lbs	18 feet	120°	30	24

## **CONTROL BOARDS**

2302A24U2DGR

Release with key

DESCRIPTION 2302A24U2DG USER 2 - 24V DG with plastic enclosure

USER 2 - 24V DG Replace (only circuit)





23106305 BAT7

with box (7AH)

12715070

BRA

16700047 G-LOCK Magnetic Lock



## LOCK KIT 12V

Electric lock
Counter-plate for
horizontal or vertical
mounting external and
internal cylinder





Adjustable back bracket to screw n.2 pcs







23101104 ESUN Q Battery charger 800 mA with solar panel admin



12710855 Aluminium oscillating back fixing fork

12710960 Oscillating front joint bracket for down hill installations

12715100 KEY ALPHA with special key

